



10001
10002

鎢鋼/高速鋼 塊規



Nominal Dimension (mm) 公稱尺寸	Dimension (mm) 尺寸
≥0.5~10	30 x 9
≥10~500	35 x 9

- As standard specification to measure the height or linear calibration, It can be corrected, check or adjust the precision of the measuring and excellent wear resistance.
- Material: Hardness of High-speed steel HRC $\geq$ 63°
Hardness of tungsten steel HRC75 $\pm$ 2°
- 適用於作為高度或直線量測校驗規範。
可校正、檢查或調整量具的精密度。
- 經過特殊熱處理過，具有高硬度和耐磨性極佳。
- 材質: 高速鋼硬度HRC $\geq$ 63°
鎢鋼K20 HRC75 $\pm$ 2°

Unit: mm

NO 訂購編號	Total blocks 總塊數	Class 級別	Nominal Dimension (mm) 公稱尺寸	Steps (mm) 間隔	NO. of blocks 塊數
10001-1	DM-112 T	0	1.0005	—	1
10001-2	DM-112 T	1	1.001-1.009	0.001	9
10001-3	DM-103 T	0	1.01-1.49	0.01	49
10001-4	DM-103 T	1	0.5-24.5	0.5	49
10001-5	DM-87 T	0	25-100	25	4
10001-6	DM-87 T	1	1.005	—	1
			1.01-1.49	0.01	49
			0.5-24.5	0.5	49
			25-100	25	4
			1.001-1.009	0.001	9
			1.01-1.49	0.01	49
			0.5-9.5	0.5	19
			10-100	10	10

NO 訂購編號	Total blocks 總塊數	Class 級別	Nominal Dimension (mm) 公稱尺寸	Steps (mm) 間隔	NO. of blocks 塊數
10002-1	DM-112	0	1.0005	—	1
10002-2	DM-112	1	1.001-1.009	0.001	9
10002-3	DM-112	2	1.01-1.49	0.01	49
10002-4	DM-103	0	0.5-24.5	0.5	49
10002-5	DM-103	1	25-100	25	4
10002-6	DM-103	2	1.005	—	1
10002-7	DM-87	0	1.01-1.49	0.01	49
10002-8	DM-87	1	0.5-24.5	0.5	49
10002-9	DM-87	2	25-100	25	4
10002-10	DM-47	0	1.001-1.009	0.001	9
10002-11	DM-47	1	1.01-1.49	0.01	49
10002-12	DM-47	2	0.5-24.5	0.5	19
10002-13	DM-38	0	10-100	10	10
10002-14	DM-38	1	1.005	—	1
10002-15	DM-38	2	1.01-1.09	0.01	9
10002-16	DM-8 (B)	0	1.1-1.9	0.1	9
10002-17	DM-8 (B)	1	1-24	1	24
10002-18	DM-8 (B)	2	25-100	25	4
10002-19	DM-8 (S)	0	1.005	—	1
10002-20	DM-8 (S)	1	1.01-1.09	0.01	9
10002-21	DM-8 (S)	2	1.1-1.9	0.1	9
			10-100	10	10
			125-200	25	4
			250	—	1
			300-500	100	3
			25-200	25	8