

SL series

Economical and High-accuracy Type

特性 Features :

- 此機台適合加工各種外徑尺寸圓棒，屬經濟型機種。
- 後座搭載動力馬達於鑽孔時傳動加工物，鑽孔同心度表現更佳。
- 配置手動三爪夾頭，另可依據加工物選配油壓夾頭。
- These types of machines are economical and suitable to drill many kinds of round bars.
- Equipped with the motor in the rear of machine, the motor drives workpiece counter-rotating to increase concentricity.
- Using manual three-jaw chuck to fix round bars, also be equipped with hydraulic chucks per job.



型號 Model	SL series	
控制器 Controller	CNC / NC	
主軸數 Spindle number	1~4	
鑽孔範圍 Drilling diameter	ø2-ø6mm / ø3-ø12mm / ø10-ø25mm / ø20-ø50mm	
鑽孔深度 Drilling depth (Z)	300 / 500mm / 1,000mm / 1,500mm / 2,000mm	
進給速 Drilling feed	10-250mm/min	
主軸轉速 Spindle rpm	0~6,000	
切削油壓 Pressure	0~100kg/cm ²	
出油量 Outflow	30~100L/min	
油箱 Oil tank	800L~1,400L	
固定裝置 Fixture device	手動夾頭 / 油壓夾頭 Manual chuck /Hydraulic chuck	
其他 Other design	工件逆轉動 Workpiece counter-rotating	

經濟型、高精度


SL-500B




SL-500



人機操作介面
HMI control panel



夾持旋轉系統
Clamping & Rotating system



油壓夾持系統
Hydraulic clamping system



SL-1200