

STRAIGHT PU HOSE :

Metric Units

Part No.	I.D(mm)	O.D(mm)	Length	Temperature	Working Pressure at 23 °C(73.4 °F)
HUS2504	2.5	4	200M	-20 °C ~ 60 °C (-5 °F ~ +140 °F)	150PSI (10Bar/1MPa)
HUS0406	4	6	200M		
HUS0508	5	8	100M		
HUS6510	6.5	10	100M		135PSI(9Bar/0.9MPa)
HUS0812	8	12	100M		
HUS1014	10	14	50M		100PSI (7Bar/0.7MPa)
HUS1216	12	16	50M		
HUS95135	9.5	13.5	50M		

Imperial Units

Part No.	O.D(inch)	I.D(inch)	Length	Temperature	Working Pressure at 23 °C(73.4 °F)
HUS104160	1/4"	0.16"	100	-20 °C ~ 60 °C (-5 °F ~ +140 °F)	150PSI(10Bar/1MPa)
HUS516187	5/16"	0.187"	100		135PSI (9Bar/0.9MPa)
HUS308250	3/8"	0.25"	50		
HUS102320	1/2"	0.32"	50		
HUS916375	9/16"	0.375"	50		

Standard Color: ●RD ●OR ●YL ●GN ●BS ●BK

FEATURES :

- 1.Super mechanical strength and excellent abrasive resistance.
- 2.Superior heat and cold resistance.
- 3.Oil resistance.
- 4.Light weight.
- 5.Could accept custom-made.
(Packing, or Length and can connect with different fitting or coupler.)
- 6.Meet the international norms : ISO 14743 , ISO 14746

